

High quality electron beams from a plasma channel guided laser wakefield accelerator

C.G.R. Geddes^{1,2}, Cs. Toth¹, J. van Tilborg^{1,3}, E. Esarey¹, C.B. Schroeder¹, D.

Bruhwyler⁴, C. Nieter⁴, J. Cary^{4,5}, and W.P. Leemans¹

¹ Lawrence Berkeley National Laboratory, 1 Cyclotron Road, Berkeley CA 94720.

² University of California, Berkeley, Berkeley CA 94720.

³ Technische Universiteit Eindhoven, Postbus 513, 5600 MB Eindhoven, the Netherlands.

⁴ Tech-X Corporation, 5621 Arapahoe Ave. Suite A, Boulder CO, 80303

⁵ University of Colorado, Boulder CO, 80309

Laser driven accelerators, in which particles are accelerated by the electric field of a plasma wave driven by an intense laser, have demonstrated accelerating electric fields of hundreds of GV/m¹⁻³. These fields are thousands of times those achievable in conventional radiofrequency (RF) accelerators, spurring interest in laser accelerators as compact next generation sources of energetic electrons and radiation^{4,5}. To date however, acceleration distances have been severely limited by lack of a controllable method for extending the propagation distance of the focused laser pulse. The ensuing short acceleration distance results in low energy beams with 100% electron energy spread¹⁻³, limiting applications. Here we demonstrate that a relativistically intense laser can be guided by a preformed plasma density channel and that the longer propagation distance can result in electron beams of percent energy spread with low emittance and increased energy, containing $>10^9$ electrons above 80 MeV. The preformed plasma channel technique forms the basis of a new class of accelerators, combining beam quality comparable to RF accelerators with the high gradients of laser accelerators to produce compact tunable high brightness electron and radiation sources.

Previous laser driven plasma acceleration experiments have used a single intense ($10^{18} - 10^{19}$ W/cm²) laser pulse propagating in the plasma formed when the front edge of the pulse ionized the gas plume emanating from a jet. The laser power was above the

critical power for self-focusing and the laser pulse length exceeded the plasma period⁶. In this so called self-modulated wakefield regime⁶ some self-guiding of the laser pulse occurs due to relativistic modification of the plasma refractive index, but the laser pulse is highly unstable⁷. Large plasma waves, or wakes, can be driven by the radiation pressure of the intense laser, but the propagation length is limited to little more than the diffraction or Rayleigh length Z_R ⁸. The best results have hence been obtained by increasing the laser spot size to increase Z_R , requiring ever greater laser power, but this approach has still been limited to distances of a few hundred micron⁸. Plasma electrons were trapped and accelerated in the resulting high amplitude plasma wave, and electron bunches with 100% energy spread and an exponentially small fraction of electrons at high energy were observed. For example, using a 32 TW laser bunches with more than 10^{10} electrons were produced but less than 1% were above 60 MeV². The beam divergence was typically greater than 50 mrad full width half maximum (FWHM). While these beams are useful for some users⁹, many applications including high energy physics and radiation sources require monoenergetic beams (percent energy spread or less) with at least 10^9 electrons¹⁰⁻¹³.

In the experiments reported here a pre-formed plasma channel, with a radially symmetric density profile that has a minimum on the laser propagation axis, was used to guide the ultra-intense drive laser pulse, circumventing the limits imposed by diffraction¹⁴. For optimum acceleration, accelerator length should be matched to the dephasing length, which is the distance it takes the accelerated electrons to outrun the plasma wave and slip into decelerating phase¹⁵. At high densities, where the laser pulse length is longer than the plasma wavelength, the laser can self-modulate resulting in large plasma waves that trap particles from the bulk plasma. In a distance on the order of 2 mm, peak energy gain can be on the order of a few hundred MeV². With controlled injection^{16,17} lower densities could be used in the future. The dephasing length and maximum energy increase as density decreases, so that accelerator lengths of several cm

and energies up to several GeV/stage are then possible⁵. To reach high intensities with a typical 10 TW peak power laser system operating at 800 nm, the laser pulse must be focused to spot sizes near 8 μm , giving $Z_R \sim 200 \mu\text{m}$ and necessitating guiding over many Z_R in order to reach the dephasing condition and high energies. A parabolic transverse density profile can be matched to guide a Gaussian laser mode without distortion in the low intensity limit, and guiding has been previously demonstrated¹⁸⁻²¹ over many Z_R at input intensities below $2 \times 10^{17} \text{ W/cm}^2$. Such intensities are too low to trap and accelerate electrons. Here we report the first guiding of a relativistically intense laser (10^{19} W/cm^2 input intensity) over a distance of 10 Z_R , and the resultant production of high quality electron beams. Much as in a RF accelerator where cavities provide confinement and field shaping for the RF-power, the plasma channel guides the laser beam and transversely shapes the plasma wakes.

The present experiments used the multi arm l'OASIS Ti:Sapphire laser^{22,23}, operating at a wavelength of 810 nm with chirped pulse amplification²⁴, to form a guiding channel using a variation of the ignitor-heater method¹⁹ and to drive the plasma wake (Fig. 1). By adjusting the energy and the timing of the guide formation pulses, the channel profile was matched to guide the drive pulse without distortion over 10 Z_R at input powers up to 4 TW ($4 \times 10^{18} \text{ W/cm}^2$). Guiding efficiency at 4 TW was 35%, a reduction of 20% compared to the low power case (0.5 TW), suggesting that a significant amount of laser energy was depleted by excitation a plasma wave. No electrons were accelerated at 4 TW, offering the exciting possibility of using laser injection for the controlled trapping of electrons in this plasma wave without 'dark current'^{16,17}.

Electrons were trapped and accelerated using a 9 TW drive pulse, and optimal performance was found in channels detuned slightly from the low power guiding condition, with 40% less rise in density over the spot diameter than a matched

channel¹⁹. The contribution of relativistic self guiding present for the high intensity pulse may be responsible for these changes. At 9 TW the mode image showed an intense output spot of 24 μm FWHM (Fig. 2b), slightly larger than the input spot but much smaller than the unguided pulse (Fig. 2d). Enlargement of the output spot compared to the input and leakage outside the guide appeared as the input intensity was increased well beyond the relativistic self focusing threshold, and are due to the inability of the channel to perfectly control the spot size in the presence of self guiding. Correlation of the mode imager and interferometer measurements showed that an intense guided mode was present only when the interferometer indicated that the laser was well confined to the channel (Fig. 2a). The axial plasma density was within 10% of $1.9 \times 10^{19} \text{ cm}^{-3}$ over the central 1.7 mm of the jet and the drive laser pulse was thus a factor of two longer than the linear plasma period, i.e. in the self-modulated regime⁶. This regime was chosen to allow comparison to unchannelled experiments, and also because the slower phase velocity of the wake at high plasma density allows trapping of background plasma electrons yielding high charge electron beams without a separate injector.

As shown in Fig. 3, the channel guided accelerator produced high charge electron beams with small energy spread at high energy, a unique feature that has not been observed in previous laser plasma acceleration experiments. To obtain the beam charge, the spectrometer phosphor screen has been calibrated against an ICT and against radionuclide activation measurements⁹, both of which are consistent. For the data shown in Fig. 3, the $\pm 2\%$ energy spread of the peak centered at 86 MeV is essentially limited by the spectrometer resolution so that the beam may in fact have narrower energy spread. The divergence of the bunch at 86 MeV was half that of the integrated beam observed on the phosphor before the magnet, consistent with previous experiments that have shown that higher energy electrons were more collimated². The bunch shows a contrast ratio greater than 10:1 above a broad distribution of charge

extending on either side. Space charge effects should be minimal for this relativistic beam, so assuming ballistic propagation from a source the size of the laser spot in the channel (8.5 μm at entrance, 24 μm at exit), an upper limit for the emittance can be obtained. Femtosecond bunches have hence been produced²⁵ containing 2×10^9 electrons with geometric and normalized RMS emittances ϵ_x below 0.05 to 0.01 $\pi\text{-mm-mrad}$ and below 1 to 2 $\pi\text{-mm-mrad}$ RMS, respectively. The peak current is on the order of 10 kA with emittance comparable to the best state of the art RF facilities¹¹. Bunches with energy up to 150 MeV have been observed on separate shots (see below).

Two dimensional simulations using the particle in cell (PIC) code VORPAL²⁶ with parameters close to the experiment indicate that the high quality electron bunches observed may be formed by a combination of pulse evolution, beam loading, and dephasing. As the drive laser pulse propagates through the plasma it self modulates, driving an intense plasma wake that traps electrons. The initial bunch of trapped electrons induces a secondary wake which interferes with the primary wake, reducing its amplitude²⁷. If the drive laser pulse energy is just above the threshold for trapping, this beam loading effect suppresses further injection creating an electron bunch isolated in phase space. The trapped electrons are then accelerated until they outrun (dephase from) the wake, at which point they are concentrated in phase and energy, forming a high quality low energy spread bunch (Fig. 4). Matching accelerator length and dephasing length to obtain high quality bunches with the parameters (jet length and Z_R) of this experiment required maintaining the intensity of the laser over many Z_R using a guiding channel. This dephasing condition can alternatively be met by a short plasma at high density (see below) or by using a larger laser spot size to extend Z_R , but these alternatives are less efficient since high density lowers peak energy while large spot size requires many times greater laser power. Fluid²⁸ and other PIC²⁹ simulations have also observed that longer acceleration length results in narrow energy spread. Only one accelerating bucket contributes to the high energy beam due to beam loading in these

simulations, so that the bunch length is less than a plasma period; for the experimental parameters the bunch length is near 10 fs FWHM.

The quality of optical guiding as well as the pointing, quality, and charge of the electron beams at high energy fluctuated shot to shot, likely caused by laser pointing jitter that changes the overlap between the wake drive pulse and the channel formation pulses (and hence guide quality and incoupling) as well as laser power fluctuations. Beams with 3×10^9 electrons have been observed at similar energies (78 ± 3 MeV FWHM), and electrons were observed up to the limit of our 55 degree high resolution spectrometer (92 MeV). Using a separate phosphor screen placed after the magnet at a 5 degree angle to the beam we observed bunches at energies up to 150 MeV, but this diagnostic does not allow the fine resolution required to resolve energy spread. Structure in the energy spectrum has been seen for electrons with energy as low as 15 MeV. Below 15 MeV there is an essentially continuous distribution, and total beam charge was 1.7×10^{10} electrons as measured by the ICT, subtending $f/8$. Using a bend magnet, the low energy contribution can be separated, leaving a high energy high quality beam with a few 10^9 electrons. Consistent control of guiding and electron injection^{16,17} in order to stabilize these beams are among the next challenges for laser accelerators.

To provide a baseline for evaluating the effects of guiding, the accelerator was operated with the same gas jet and laser but without the guiding channel. As seen in Fig 2 c and d, the laser pulse diffracted strongly, limiting the acceleration length. The electron beam had a total charge of 1.5×10^{10} electrons, as measured by the ICT, with divergence near 50 mrad FWHM. The electron energy spectrum is described by a two-temperature Boltzmann distribution characterized by a 2.6 MeV temperature below 10 MeV and an 8 MeV temperature above 10 MeV. Structure in the energy spectrum did occur occasionally in the tail of the distribution above 15 MeV containing $< 2\%$ of

the charge, consistent with a beam accelerated over a short distance and with previous experiments^{1,2,9}. No electrons were observed above 40 MeV on the spectrometer phosphor screen (detection threshold 10^7 electrons). Plasma density was independently optimized for the unchannelled accelerator, and highest charge and electron energies were obtained at $4 \times 10^{19} \text{ cm}^{-3}$. The high density allowed acceleration before the laser diffracted since self modulation and dephasing both occur more quickly at high density, but this also reduced the peak energy compared to the channelled case. Operating the unchannelled accelerator at the density used for the channelled accelerator ($2 \times 10^{19} \text{ cm}^{-3}$), produced low charge low energy beams, since the intensity of the drive beam was not maintained for sufficient distance to allow acceleration at this density without channelling. Using a 600 μm long plasma at $4 \times 10^{19} / \text{cm}^3$, which is close to the dephasing length observed in PIC simulations at this density, the un channelled accelerator produced the same peak energy as in the 2 mm plasma, but with more structure in the spectrum. These results confirm that matching accelerator length to dephasing length is critical for structuring the spectrum, and that extending the length (for instance using a channel at lower density) results in higher energies.

To differentiate the effects of channeling from pre-ionization, the ignitor pulse was fired 80 ps before the drive pulse. The plasma does not expand significantly over 80 ps, so there was no shock wave and the transverse density profile was flat and had no guiding properties. We observed no difference between the drive pulse only and pre-ionized cases, indicating that channeling and not pre-ionization was responsible for differences in the electron beams described above.

The beams from channel guided accelerators such as those described here, with a few 10^9 electrons in percent level energy spread and mrad divergence as well as intrinsic synchronization to the laser beam, open up a new class of experiments with laser accelerators. The channelling technology offers the ability to control the laser

beam propagation much as a copper structure provides guiding and field shaping to RF accelerators. The investment of power in channel formation is less than 5% of the drive pulse power (20% of the energy), yet spectral density of these beams near 80 MeV is at least a factor of 200 above previous unchannelled experiments using several times the laser power, and peak energy observed is comparable ². The narrow energy spread of the channel produced beams is consistent with simulations which also indicate that the bunch length is near 10 fs. The channel guided laser accelerator technique will hence allow efficient generation of femtosecond x-rays¹⁰, coherent THz and infrared radiation^{13,30}, and is an essential step towards the development of compact multi stage electron accelerators with ultrafast bunches and with focusability and luminosity competitive with state of the art RF accelerators.

<received> Style tag for received and accepted dates (omit if these are unknown).

1. Modena, A. et al. Electron Acceleration from the Breaking of Relativistic Plasma Waves. *Nature* **377**, 606-608 (1995).
2. Malka, V. et al. Electron acceleration by a wake field forced by an intense ultrashort laser pulse. *Science* **298**, 1596-1600 (2002).
3. Leemans, W. P. et al. Electron-yield enhancement in a laser-wakefield accelerator driven by asymmetric laser pulses - art. no. 174802. *Physical Review Letters* **89**17, 4802 (2002).
4. Tajima, T. & Dawson, J. M. Laser electron accelerator. *Physical Review Letters* **43**, 267-70 (1979).
5. Esarey, E., Sprangle, P., Krall, J. & Ting, A. Overview of Plasma-Based Accelerator Concepts. *IEEE Transactions on Plasma Science* **24**, 252-288 (1996).

6. Esarey, E., Krall, J. & Sprangle, P. Envelope Analysis of Intense Laser Pulse Self-Modulation in Plasmas. *Physical Review Letters* **72**, 2887-2890 (1994).
7. Esarey, E., Sprangle, P., Krall, J. & Ting, A. Self-Focusing And Guiding Of Short Laser Pulses In Ionizing Gases And Plasmas [Review]. *IEEE Journal of Quantum Electronics* **33**, 1879-1914 (1997).
8. Najmudin, Z. et al. Self-modulated wakefield and forced laser wakefield acceleration of electrons. *Physics of Plasmas* **10**, 2071-2077 (2003).
9. Leemans, W. P. et al. Gamma-neutron activation experiments using laser wakefield accelerators. *Physics of Plasmas* **8**, 2510-2516 (2001).
10. Catravas, P., Esarey, E. & Leemans, W. P. Femtosecond x-rays from Thomson scattering using laser wakefield accelerators. *Measurement Science & Technology* **12**, 1828-1834 (2001).
11. Wang, X. J., Qiu, X. & Ben-Zvi, I. Experimental observation of high-brightness microbunching in a photocathode RF electron gun. *Physical Review E. Statistical Physics, Plasmas, Fluids, & Related Interdisciplinary Topics* **54**, R3121-4 (1996).
12. Schoenlein, R. W. et al. Femtosecond X-Ray Pulses at 0.4 Angstrom Generated by 90-Degrees Thomson Scattering - a Tool for Probing the Structural Dynamics of Materials. *Science* **274**, 236-238 (1996).
13. Leemans, W. P. et al. Observation of terahertz emission from a laser-plasma accelerated electron bunch crossing a plasma-vacuum boundary - art. no. 074802. *Physical Review Letters* **9107**, 4802 (2003).

14. Sprangle, P., Esarey, E., Krall, J. & Joyce, G. Propagation and guiding of intense laser pulses in plasmas. *Physical Review Letters* **69**, 2200-3 (1992).
15. Leemans, W. P. et al. Plasma Guiding and Wakefield Generation for Second-Generation Experiments. *IEEE Transactions on Plasma Science* **24**, 331-342 (1996).
16. Umstadter, D., Kim, J. K. & Dodd, E. Laser Injection of Ultrashort Electron Pulses into Wakefield Plasma Waves. *Physical Review Letters* **76**, 2073-2076 (1996).
17. Esarey, E., Hubbard, R. F., Leemans, W. P., Ting, A. & Sprangle, P. Electron Injection into Plasma Wake Fields by Colliding Laser Pulses. *Physical Review Letters* **79**, 2682-2685 (1997).
18. Durfee, C. G. & Milchberg, H. M. Light Pipe for High Intensity Laser Pulses. *Physical Review Letters* **71**, 2409-2412 (1993).
19. Volfbeyn, P., Esarey, E. & Leemans, W. P. Guiding of laser pulses in plasma channels created by the ignitor-heater technique. *Physics of Plasmas* **6**, 2269-2277 (1999).
20. Kim, K. Y., Alexeev, I., Fan, J., Parra, E. & Milchberg, H. M. in *AIP Conf. Proc.*, **647**, 646 (2002).
21. Gaul, E. W. et al. Production and characterization of a fully ionized He plasma channel. *Applied Physics Letters* **77**, 4112-4114 (2000).
22. Toth, C. et al. Powerful, pulsed, THz radiation from laser accelerated relativistic electron bunches. *SPIE Proceedings* 5448 (2004).

23. Leemans, W. P. et al. Laser-Driven Plasma-Based Accelerators - Wakefield Excitation, Channel Guiding, and Laser Triggered Particle Injection. *Physics of Plasmas* **5**, 1615-1623 (1998).
24. Strickland, D. & Mourou, G. Compression of amplified chirped optical pulses. *Optics Communications* **56**, 219-21 (1985).
25. Schroeder, C. B., Esarey, E., van Tilborg, J. & Leemans, W. P. Theory of coherent transition radiation generated at a plasma-vacuum interface - art. no. 016501. *Physical Review E* **6901**, 6501 (2004).
26. Nieter, C. & Cary, J. R. VORPAL: a versatile plasma simulation code. *Journal of Computational Physics* **196**, 448-473 (2004).
27. Katsouleas, T., Wilks, S., Chen, S., Dawson, J. M. & Su, J. J. Beam loading in plasma accelerators. *Particle Accelerators* **22**, 81-99 (1987).
28. Reitsma, A. J. W. et al. Simulation of electron postacceleration in a two-stage laser wakefield accelerator - art. no. 051301. *Physical Review Special Topics-Accelerators & Beams* **505**, 1301 (2002).
29. F.S. Tsung et al, submitted to Physical Review Letters.
30. Saes, M. et al. A setup for ultrafast time-resolved x-ray absorption spectroscopy. *Review of Scientific Instruments* **75**, 24-30 (2004).

ACKNOWLEDGEMENTS: Work supported by the U.S. Dept. of Energy; C.Geddes also supported by Hertz foundation. C. Geddes acknowledges his faculty advisor Jonathan Wurtele, at UC Berkeley. We appreciate contributions from Gerry Dugan, Jerome Faure, Gwenael Fubiani, Bob Nagler, Kei Nakamura, Ned Saleh, Brad Shadwick, Leon Archambault, Michael Dickinson, Scott Dimaggio, Don Syversrud, Joe Wallig, and Nathan Ybarrolaza.

Correspondence and requests for materials should be addressed to W.P.L. (e-mail: wpleemans@lbl.gov).

Fig. 1. In the channel guided laser wakefield accelerator, the plasma channel was formed in a supersonic hydrogen gas jet (2.4 mm long at an atomic density of $4.5 \times 10^{19} \text{ cm}^{-3}$) by two pulses fired 500 ps before the drive pulse. A cylindrical filament of plasma was ionized by an intense (60 fs, 15 mJ) ignitor pulse, collinear with the pulse which drives the plasma wave and focused at f/15 near the downstream edge of the gas jet. The plasma was subsequently heated to tens of eV by inverse Bremsstrahlung, using a long (250 ps, 150 mJ) pulse incident from the side for efficient heating. The resulting hot plasma filament on axis expanded outward, driving a shock wave. This shock resulted in a density depletion on axis and a nearly parabolic transverse density profile which was tuned by adjusting the timing and energies of the beams. The plasma wave was driven by a 500 mJ pulse of 55 fs FWHM, focused at the upstream edge of the channel to an $8.5 \text{ }\mu\text{m}$ FWHM spot by an f/4 off axis parabola giving an intensity of $1.1 \times 10^{19} \text{ W/cm}^2$. Propagation of the laser was monitored with a side interferometer and mode imager CCD. The electron beam accelerated by the plasma wave was analyzed using an integrating current transformer (ICT), a phosphor screen, and a magnetic spectrometer (55 degree bend angle used for high resolution at energy $< 92 \text{ MeV}$, 5 degree for higher energies).

Fig. 2. Laser propagation with and without channel. The plasma size after the propagation of the drive pulse shows the radial extent of ionization, indicating the extent of diffraction of the laser as it propagates through the plasma. The profile of the laser spot at the exit of the plasma was viewed using a solid mirror

inserted into the beamline and an f/10 achromatic lens that imaged the laser spot directly onto a CCD (mode imager) camera providing 10 μm resolution. In the channel guided accelerator, the plasma (a) was similar to the guiding channel indicating that the drive laser pulse was confined to the channel. The laser mode at the channel exit is a well defined spot of 24 μm FWHM containing 10% of the input energy (b). This indicates the effectiveness of the channel in maintaining the drive beam intensity and mode over many diffraction lengths. The spot is circular, confirming that the guiding channel is cylindrically symmetric. The reduction in energy from the input spot is due to a combination of leakage from the channel and depletion of the laser energy to excite the wake. When the channel was off, the interferometer showed blow out of the drive pulse after a few hundred microns (c), and the mode imager showed a diffuse transmitted spot(d).

Fig. 3. Single shot electron beam spectrum and divergence of the channel guided accelerator, showing a bunch containing 2×10^9 electrons in a narrow distribution at 86 ± 1.8 MeV and 3 mrad divergence FWHM with contrast $> 10:1$ above background. This distribution is qualitatively different from the exponential distribution obtained in past (unchanneled) laser acceleration experiments. The magnetic spectrometer consists of a slit 82 cm from the gas jet, a bend of 55° in a dipole magnet to provide dispersion, and a phosphor screen (LANEX Fast backed by an aluminum foil to reject laser light) imaged by a CCD camera. Single shot energy range is $\pm 15\%$ about a central value selectable from 1 to 80 MeV, and resolution is $dE/E = \pm 2\%$. The vertical beam

size is obtained in the undispersed direction, allowing the simultaneous determination of (vertical) divergence and energy. Since electron beams observed on the phosphor before the magnet were typically round in shape, this vertical divergence measurement is representative. Charge density is plotted in electrons/MeV/Steradian.

Fig. 4. Particle in cell simulations, here displaying the phase space of the electrons, show an energy distribution similar to that in the experiments. A high quality electron bunch is formed when the acceleration length is matched to the dephasing length, and when the laser strength is such that beam loading is sufficiently strong to turn off injection after the initial bunch of electrons is loaded. The peak energy observed in the simulations is 200 MeV, close to the experimental result.







